




finished wall thickness **100** or **125** mm



### Sliding door systems for single doors

Frame for a single sliding pocket door - the simple answer to create more space in any room



**N.B.** Non standard sizes on request

FRAMES FOR SINGLE DOORS			DOOR PANEL UK standard		NOTES
Max. Passage Size PW x PH	Overall Dimension W x H	Finished Wall	DW	DH	
600 x 2030	1288 x 2115	100 or 125	626	2040	Suitable for use with 35 - 44 mm thick doors Max. door weight 80 kg. (120 kg. on request)  When fitting flush pull handles we recommend the stop be regulated so the door protrudes from the pocket to avoid risk to fingers. Should the door be set to enter the pocket completely we do not accept any liability.  Doors, plasterboard and final architrave not supplied.
700 x 2030	1488 x 2115	100 or 125	726	2040	
800 x 2030	1688 x 2115	100 or 125	826	2040	
900 x 2030	1888 x 2115	100 or 125	926	2040	
1000 x 2030	2088 x 2115	100 or 125	1026	2040	
585 x 1971	1273 x 2056	100 or 125	2ft. 0in. x 6ft. 6in. (610 x 1981mm)		
661 x 1971	1449 x 2056	100 or 125	2ft. 3in. x 6ft. 6in. (686 x 1981mm)		
737 x 1971	1625 x 2056	100 or 125	2ft. 6in. x 6ft. 6in. (762 x 1981mm)		
813 x 1971	1701 x 2056	100 or 125	2ft. 9in. x 6ft. 6in. (838 x 1981mm)		
900 x 1971	1888 x 2056	100 or 125	3ft. 0in. x 6ft. 6in. (914 x 1981mm)		

dimensions are given in mm.

### ADVANTAGES - The counterframes by ECLISSE are:

- **STRENGTH** - These are the strongest sliding door frames of this type on the market
- **PRACTICAL** - Very easy to assemble and simple to fit
- **EXTRACTABLE TRACK** - No need to break into the wall for track maintenance